

C.I.P.	Pistol and revolver cartridges	TABLE	IV
		DATE	84-06-14
		REV.	02-05-15

Calibres of rifled short weapons for pistol and revolver cartridges.
The metric calibres are classed before the calibres originally designated in inches.
The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

Calibre	Country of origin	Date	Rev.	M	PTmax	PK	PE
5,45 x 18	SU	93-05-24	00-06-07	9	1750	2015	2275
5,75 Velodog	FR	84-06-14	00-06-07	17,5	680	782	885
6,35 Browning	BE	84-06-14	00-06-07	9	1200	1380	1560
7 x 49 GJW	DE	91-02-19	00-06-07	25	4700	5405	6110
7,5 Ord. Suisse	CH	84-06-14	00-06-07	12,5	1850	2128	2405
7,62 x 25 Tokarev	SU	90-04-14	00-06-07	17,5	2400	2760	3120
7,62 Nagant	BE	84-06-14	00-06-07	17,5	770	886	1001
7,63 Mauser	DE	84-06-14	00-06-07	17,5	2600	2990	3380
7,65 Browning	BE	84-06-14	00-06-07	10,5	1600	1840	2080
7,65 Long	FR	92-04-17	00-06-07	10,5	1650	1898	2145
7,65 Parabellum	DE	84-06-14	00-06-07	12,5	2350	2703	3055
8 mm Gasser	AT	84-06-14	00-06-07	12,5	1000	1150	1300
8 mm Lebel	FR	84-06-14	00-06-07	12,5	1250	1438	1625
8 mm Steyr	AT	84-06-14	00-06-07	10,5	2100	2415	2730
9 x 18	DE/AT	84-06-14	00-06-07	9	1800	2070	2340
9 mm Makarov	SU	91-09-20	00-06-07	10,5	1600	1840	2080
9 mm Browning court	BE	84-06-14	00-06-07	9	1350	1553	1755
9 mm Browning long	BE	84-06-14	00-06-07	10,5	1650	1898	2145
9 mm FAR	IT	00-09-15		12,5	2600	2990	3380
9 mm FX & CQT	CA	98-01-27	00-06-07	12,5	350	403	455
9 mm Luger	DE	84-06-14	00-06-07	12,5	2350	2703	3055
9 x 21	IL	84-06-14	00-06-07	12,5	2350	2703	3055
9 mm Steyr	AT	84-06-14	00-06-07	12,5	1350	1553	1755
9 x 22 MJR	AT	93-12-13	00-06-07	12,5	2550	2933	3315
9 x 25 Super Auto G	AT	91-05-17	00-06-07	12,5	2550	2933	3315
10 mm Auto	SE	84-10-03	00-06-07	12,5	2300	2645	2990
10 mm FAR	IT	00-09-15		12,5	2250	2590	2925
10,4 Ord. It.	IT	84-06-14	00-06-07	10,5	630	725	819
11 mm 73	FR	02-01-22		19,5	1150	1323	1495
22 PICRA	CZ	99-03-15	00-06-07	17,5	3200	3680	4160
22 Rem.Jet Mag.	US	84-06-14	00-06-07	10,5	2550	2933	3315
221 Rem. Fireball	US	84-06-14	00-06-07	17,5	3200	3680	4160
260 PICRA	CZ	99-03-15	00-06-07	17,5	3900	4485	5070
30 PICRA	CZ	99-04-20	00-06-07	17,5	2800	3220	3640
30-357 AeT	IT	00-09-12	02-05-15	17,5	3000	3450	3900

(suite)

PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,30 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Rem. = Remington

Mag. = Magnum

S&W = Smith and Wesson

Wad Cut = Wad Cutter

Ord.It. = Ordonance Italienne

Win. = Winchester

N.P. = New Police

Spl. = Spezial

ACP = Auto Colt Pistol

C.I.P.	Pistol and revolver cartridges	TABLE	IV
		DATE	84-06-14
		REV.	02-05-15

Calibres of rifled short weapons for pistol and revolver cartridges.
The metric calibres are classed before the calibres originally designated in inches.
The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

(Suite)

Calibre	Country of origin	Date	Rev.	M	PTmax	PK	PE
32 H. & R. Mag.	US	86-02-25	00-06-07	12,5	1400	1610	1820
32 Long Colt	US	84-06-14	00-06-07	12,5	1000	1150	1300
32 Short Colt	US	84-06-14	00-06-07	9,5	1000	1150	1300
32 S.& W.	US	84-06-14	00-06-07	8	900	1035	1170
32 S.& W. Long N.P.	US	84-06-14	00-06-07	12,5	1000	1150	1300
32 S & W. Long Wad Cut.	DE/FI	84-06-14	00-06-07	8	1550	1783	2015
320 Long	GB	84-06-14	00-06-07	12,5	1000	1150	1300
320 Short	GB	84-06-14	00-06-07	10,5	1200	1380	1560
357 Auto Mag.	US	84-06-14	00-06-07	17,5	2550	2933	3315
357 Magnum	US	84-06-14	00-06-07	17,5	3000	3450	3900
357 Maximum	US	84-06-14	00-06-07	25	3100	3565	4030
357 SIG	US	95-03-09	00-06-07	10,5	3050	3508	3965
38 Long Colt	US	84-06-14	00-06-07	10,5	900	1035	1170
38 Short Colt	US	84-06-14	00-06-07	10,5	900	1035	1170
38 S.& W. et Colt N.P.	US	84-06-14	00-06-07	9	1200	1380	1560
38 Special	US	84-06-14	00-06-07	12,5	1500	1725	1950
38 Spl. AMU	US	84-06-14	00-06-07	10,5	1250	1438	1625
38 Spl. Wad Cut.	US	84-06-14	00-06-07	10,5	1200	1380	1560
38 Super Auto	US	84-06-14	02-01-22	12,5	2300	2645	2990
38/357 FX	CA	98-01-27	00-06-07	12,5	350	403	455
38-45 ACP	US	84-06-14	00-06-07	12,5	2350	2703	3055
380 Long	GB	84-06-14	00-06-07	12,5	770	886	1001
380 Short	GB	84-06-14	00-06-07	10,5	680	782	884
40 S.& W.	US	90-02-01	00-06-07	10,5	2250	2588	2925
41 ACT EXP	IL	86-12-03	00-06-07	10,5	2250	2588	2925
41 Long Colt	US	84-06-14	00-06-07	12,5	900	1035	1170
41 Rem. Mag.	US	86-12-14	00-06-07	17,5	3000	3450	3900
44 Colt	US	00-02-15	00-06-07	12,5	1000	1150	1300
44 Rem. Mag.	US	86-12-14	00-06-07	17,5	2800	3220	3640
44 S.& W. Russian	US	84-06-14	00-06-07	12,5	1000	1150	1300
44 S.& W. Special	US	84-06-14	00-06-07	17,5	1000	1150	1300

(suite)

PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,30 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Rem. = Remington

Mag. = Magnum

S&W = Smith and Wesson

Wad Cut = Wad Cutter

Ord.It. = Ordonance Italienne

Win. = Winchester

N.P. = New Police

Spl. = Spezial

ACP = Auto Colt Pistol

C.I.P.	Pistol and revolver cartridges	TABLE	IV
		DATE	84-06-14
		REV.	02-05-15

Calibres of rifled short weapons for pistol and revolver cartridges.
The metric calibres are classed before the calibres originally designated in inches.
The classification is in growing and in alphabetical order according to the designation of the calibre.

Transducer method

(Suite)

Calibre	Country of origin	Date	Rev.	M	PTmax	PK	PE
45 Auto	US	84-06-14	00-06-07	12,5	1300	1495	1690
45 Auto Rim	US	84-06-14	00-06-07	12,5	1200	1380	1560
45 Colt	US	84-06-14	00-06-07	12,5	1100	1265	1430
45 HP	AT	84-11-16	00-06-07	12,5	1300	1495	1690
45 S & W Schofield	US	00-02-15	00-06-07	12,5	1000	1150	1300
45 Win. Mag.	US	84-06-14	00-06-07	17,5	2750	3163	3575
450 Short	GB	84-06-14	00-06-07	8	720	828	936
454 Casull	US	95-03-09	00-06-07	17,5	3900	4485	5070
455 MK II	GB	84-06-14	00-06-07	7,5	900	1035	1170
50 AE	IL	91-10-18	00-06-07	10,5	2300	2645	2990

PTmax = maximum average pressure (bar)

PK = 1,15 Pmax = maximum statistical individual pressure (bar)

PE = 1,30 Pmax = mean proof pressure (bar)

M = location of the pressure take (mm)

Notice: For conformal or tangential transducers the location (M) is that defined by the manufacturer.

Rem. = Remington

Mag. = Magnum

S&W = Smith and Wesson

Wad Cut = Wad Cutter

Ord.It. = Ordonance Italienne

Win. = Winchester

N.P. = New Police

Spl. = Spezial

ACP = Auto Colt Pistol